JP09054982 OPTICAL DISK SUBSTRATE AND ITS PRODUCTION TELUIN CHEM LTD

Inventor(s): ;TOKUDA TOSHIMASA ;NAKAHIRO HIDEKI Application No. 07204619 , Filed 19950810 , Published 19970225

Abstract:

PROBLEM TO BE SOLVED: To obtain an optical disk substrate attaining accurate transfer of pits, ensuring a low error rate and less liable to warp by moisture absorption with polycarbonate resin from 2,2- bis(3-methyl-4-hydroxyphenyl)propane.

SOLUTION: This optical disk substrate is formed with polycarbonate resin obtd. by allowing a carbonate precursor to react with dihydric phenol, mainly 2,2-bis(3- methyl-4-hydroxyphenyl)propane. The specific viscosity of the polycarbonate resin is 0.2-0.4. When the resin is dissolved in methylene chloride, the number of undissolved particles each having $\geq 0.5 \mu m$ diameter measured in the resultant soln. is $\leq 25,000$ per 1g of the resin and the number of undissolved particles each having $\geq 1 \mu m$ diameter is ≤ 500 . The resin has $\leq 0.2 wt.\%$ water absorption.

Int'l Class: G11B00724 G11B00726

Priority: JP 07140585 19950607